



STARCO MP Flotrak

- 570/60R22.5



FEATURES AND BENEFITS

Wide low profile Design

- Low ground bearing pressure, giving minimal
- Field damage whilst gathering crops

Multi angle Lug Design

- Good traction and excellent self-cleaning properties

Surface Tension Breakers between Lugs

- Further Aids self-cleaning properties

High 'Net to Gross' footprint area on centre-line + Reinforced Centre Rib

- Gives good road performance without excessive centre-line wear

All Steel Carcass Construction

- Due to the inherently cool running of an all steel carcass, we are able to provide
- an excellent load carrying capacity, combined with a superior speed rating





STARCO MP Flotrak is the ideal choice for high speed Tractor and Trailer combinations – Excellent Field performance during the loading and gathering of crops, with first class road performance to deliver the goods without the need for an additional road vehicle.

MODEL NAME	STARCO MP Flotrak
TIRE SIZE	570/60R22.5
LOAD INDEX	168 Free rolling (5600 kg)
LOAD INDEX	156 Driven (4000 kg)
SPEED INDEX	E (70Km/h)
SECTION WIDTH	573
OVERALL DIAMETER	1255
ROLLING CIRCUMFERENCE	3825
INFLATION PRESSURE	3.5 bar (51 psi)
TUBELESS/TUBE TYPE	Tubeless



INFLATION	STATIC	10KM/H	20KM/H	30KM/H	40KM/H	70KM/H
1.0 bar (14 psi)	2990	2430	2080			
1.5 bar (22 psi)	4360	3520	2990	2570		
2.0 bar (29 psi)	5725	4600	3900	3345	3095	
2.5 bar (36 psi)	7095	5695	4820	4120	3810	
3.0 bar (43 psi)	8460	6785	5735	4890	4520	
3.5 bar (51 psi)	9830	7870	6645	5665	5230	4930
4.0 bar (58 psi)	11200	8960	7560	6440	5940	5600

Load in kg

STARCO Europe
Bizonvej 4
DK-8464 Galten
Tel.: +45 8754 0000
Fax: +45 8754 0010
info@starco.com
starco.com